



|                            |  |
|----------------------------|--|
| Description                | GFCI, In-Line Style with Cord                            |
| Rated Current              | 15 amps  |
| Rated Supply Voltage       | 125 Volts  |
| Frequency                  | 60 Hz  |
| Polarity                   | 2 Pole 3 Wire  |
| Tripping Current           | 4-6 mA   |
| Maximum Tripping Time      | 25 ms  |
| Ambient Temperature Range  | -35C to 66C  |
| Reset Type upon Power Loss | Automatic (also known as Passive or Latching)            |
| Color                      | Black  |
| Design                     | UL Standard 943 Class A<br>UL Listed<br>Rainproof Design |
| Plug                       | Nema L5-15p, Straight, Molded, Black                     |
| Cordage                    | 14/3 awg (ICC or NACC), SJT, Black                       |
| Receptacle (Connector)     | IEC60320 C-15A, Straight, Molded or Mounted              |
| Function                   | Test and Reset Buttons not to be used as ON/OFF switch   |

ALL DIMENSIONS ARE IN MILLIMETERS

**WORLD CORD SETS, INC.**

TEL (860)763-2100            www.WorldCordSets.com  
 FAX (860)763-1183      sales@WorldCordSets.com

TITLE  
**GFCI CORD SET, IN-LINE STYLE**

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

|               |                   |                            |          |
|---------------|-------------------|----------------------------|----------|
| SCALE<br>NONE | DATE<br>12-3-2007 | PART NO.<br>LAB3-J13C-XXXX | REV<br>- |
|---------------|-------------------|----------------------------|----------|