



Description	GFCI, In-Line Style with Cord
Rated Current	15 amps
Rated Supply Voltage	125 Volts
Frequency	60 Hz
Polarity	2 Pole 3 Wire
Tripping Current	4-6 mA
Maximum Tripping Time	25 ms
Ambient Temperature Range	-35C to 66C
Reset Type upon Power Loss	Manual (also known as Active or non-Latching)
Color	Black
Design	UL Standard 943 Class A, CUL C22.2 compliant UL, CUL listed Rainproof Design
Plug	Nema L5-15p, Straight, Molded, Black
Cordage	14/3 awg (ICC or NACC), SJT, Black
Receptacle (Connector)	IEC60320 C-15, Right Angle, Molded or Mounted, Black
Function	Test and Reset Buttons not to be used as ON/OFF switch

ALL DIMENSIONS ARE IN MILLIMETERS

**WORLD CORD SETS, INC.**

TEL (860)763-2100            www.WorldCordSets.com  
 FAX (860)763-1183      sales@WorldCordSets.com

TITLE  
**GFCI CORD SET, IN-LINE STYLE**

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE NONE	DATE 12-3-2007	PART NO. LMB3-J13BR-XXXX	REV —
---------------	-------------------	-----------------------------	----------