



| | |
|----------------------------|--|
| Description | GFCI, Plug-Head Style with Cord |
| Plug Configuration | Nema 5-15p |
| Rated Current | 13 amps |
| Rated Voltage | 125 Volts |
| Frequency | 50/60 Hz |
| Polarity | 2 Pole 3 Wire |
| Tripping Current | 4-6 mA |
| Maximum Tripping Time | 25 ms |
| Ambient Temperature Range | -35C to 66C |
| Reset Type upon Power Loss | Automatic (also known as Passive or Latching) |
| Color | Black |
| Design | UL Standard 943 Class A with open neutral protection c-ETL-us Listed (INTERTEK) Rainproof Design |
| Cordage | 16/3 SJTW, Black |
| Receptacle (Connector) | Nema 5-15R, Straight, Molded, Black |
| RoHS | RoHS compliant model is available |
| Function | Test and Reset Buttons not to be used as ON/OFF switch |

ALL DIMENSIONS ARE IN MILLIMETERS

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

| | | | |
|-------------------------------|-----------|---------------|-----|
| TITLE | | | |
| GFCI CORDSET, PLUG-HEAD STYLE | | | |
| SCALE | DATE | PART NO. | REV |
| NONE | 12-3-2007 | PAB3-22E-0120 | A |