



| | |
|----------------------------|--|
| Description | GFCI, Plug-Head Style with Cord |
| Plug Configuration | Nema 5-20p |
| Rated Current | 20 amps |
| Rated Voltage | 120 Volts |
| Frequency | 60 Hz |
| Polarity | 2 Pole 3 Wire |
| Tripping Current | 4-6 mA |
| Maximum Tripping Time | 25 ms |
| Ambient Temperature Range | -35C to 66C |
| Reset Type upon Power Loss | Automatic (also known as Passive or Latching) |
| Color | Black |
| Design | UL Standard 943 Class A with open neutral protection UL Recognized, CSA Rainproof Design |
| Cordage | 12/3 awg (ICC or NACC), SJTW - Black Jacket |
| Receptacle (Connector) | None, 2" ROJ and Strip All 1/4" |
| RoHS | RoHS compliant |
| Function | Test and Reset Buttons not to be used as ON/OFF switch |

ALL DIMENSIONS ARE IN MILLIMETERS

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

TITLE

GFCI CORD, PLUG-HEAD STYLE

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE
NONE

DATE
12-3-2007

PART NO.
PAB5-24W-0036

REV
A