



Description	RCD, Plug-Head Style with Cord
Plug Configuration	SCHUKO CEE 7/7
Rated Current	10 amps (RCD is 16 amps, C-15A is 10 amps)
Rated Voltage	220-240 Volts
Frequency	50 Hz
Polarity	2 Pole 3 Wire
Tripping Current	15 to 30 mA (maximum)
Maximum Tripping Time	30 ms
Ambient Temperature Range	-25C to 40C for RCD (+5C to 60C for cordage)
Reset Type upon Power Loss	Manual (also known as Active or non-Latching)
Color	Black
Design	GS Approval, CE, Tested by Intertek, Type A Protection grade for housing: IP54 Tested according to DIN VDE 0620-1:2005
Cordage	3x1.0 mm ² H05VV-F, Black Jacket
Receptacle (Connector)	IEC 60320 C-15A, Straight, Molded, Black
RoHS	RoHS compliant
Function	Test and Reset Buttons not to be used as ON/OFF switch

ALL DIMENSIONS ARE IN MILLIMETERS

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

TITLE

RCD CORD SET, PLUG-HEAD STYLE

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE
NONE

DATE
12-3-2007

PART NO.
R1B2-22C-XXXX

REV
A