



|                            |  |
|----------------------------|--|
| Description                | RCD, Plug-Head Style with Cord   |
| Plug Configuration         | SCHUKO CEE 7/7   |
| Rated Current              | 16 amps  |
| Rated Voltage              | 220-240 Volts  |
| Frequency                  | 50 Hz  |
| Polarity                   | 2 Pole 3 Wire  |
| Tripping Current           | 15 to 30 mA (maximum)  |
| Maximum Tripping Time      | 30 ms  |
| Ambient Temperature Range  | -25C to 40C for RCD (+5C to 60C for cordage)   |
| Reset Type upon Power Loss | Manual (also known as Active or non-Latching)  |
| Color                      | Black  |
| Design                     | GS Approval, CE, Tested by Intertek, Type A<br>Protection grade for housing: IP54<br>Tested according to DIN VDE 0620-1:2005 |
| Cordage                    | 3x1.5 mm <sup>2</sup> H05VV-F, Black Jacket  |
| Receptacle (Connector)     | SCHUKO CEE 7/7   |
| RoHS                       | RoHS compliant   |
| Function                   | Test and Reset Buttons not to be used as ON/OFF switch   |

ALL DIMENSIONS ARE IN MILLIMETERS

**WORLD CORD SETS, INC.**

TEL (860)763-2100  
FAX (860)763-1183



www.WorldCordSets.com  
sales@WorldCordSets.com

|       |                               |
|-------|-------------------------------|
| TITLE | RCD CORD SET, PLUG-HEAD STYLE |
|-------|-------------------------------|

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

|       |           |               |     |
|-------|-----------|---------------|-----|
| SCALE | DATE      | PART NO.      | REV |
| NONE  | 12-3-2007 | R1B2-23J-XXXX | A   |