



| | |
|----------------------------|--|
| Description | RCD, Plug-Head Style with Cord |
| Plug Configuration | SCHUKO CEE 7/7 |
| Rated Current | 16 amps |
| Rated Voltage | 220-240 Volts |
| Frequency | 50 Hz |
| Polarity | 2 Pole 3 Wire |
| Tripping Current | 15 to 30 mA (maximum) |
| Maximum Tripping Time | 30 ms |
| Ambient Temperature Range | -25C to 40C for RCD (+5C to 60C for cordage) |
| Reset Type upon Power Loss | Manual (also known as Active or non-Latching) |
| Color | Black |
| Design | GS Approval, CE, Tested by Intertek, Type A Protection grade for housing: IP54 Tested according to DIN VDE 0620-1:2005 |
| Cordage | 3x1.5 mm ² H05VV-F, Black Jacket |
| Receptacle (Connector) | None, 2" ROJ and Strip All 1/4" |
| RoHS | RoHS compliant |
| Function | Test and Reset Buttons not to be used as ON/OFF switch |

ALL DIMENSIONS ARE IN MILLIMETERS

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

| | | | |
|-------------------------------|-----------|---------------|-----|
| TITLE | | | |
| RCD CORD SET, PLUG-HEAD STYLE | | | |
| SCALE | DATE | PART NO. | REV |
| NONE | 12-3-2007 | R1B2-23W-XXXX | A |