



IEC 60320 C-13

Description	RCD, Plug-Head Style with Cord
Plug Configuration	AS / NZS 3112 - 10 Amp
Rated Current	10 amps
Rated Voltage	230-240 Volts
Frequency	50 Hz
Polarity	2 Pole 3 Wire
Tripping Current	30 mA
Maximum Tripping Time	30 ms
Ambient Temperature Range	(-25C to 60C for cordage)
Reset Type upon Power Loss	Manual (also known as Active or non-Latching)
Color	White
Design	Approval by Dept of Fair Trading Protection grade for housing: IP3X Tested according to AS3190/1997, AS3100/1994
Cordage	3x1.0 mm ² H07RN-F, Black Jacket
Receptacle (Connector)	IEC60320 C-13, Straight, Molded, Black
Function	Test and Reset Buttons not to be used as ON/OFF switch

ALL DIMENSIONS ARE IN MILLIMETERS

WORLD CORD SETS, INC.

TEL (860)763-2100  www.WorldCordSets.com
 FAX (860)763-1183 sales@WorldCordSets.com

TITLE
RCD CORD SET, PLUG-HEAD STYLE

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE NONE	DATE 1-29-2008	PART NO. R1W6-72A-XXXX	REV -
---------------	-------------------	---------------------------	----------