



| | |
|----------------------------|--|
| Description | RCD, In-Line Style with Cord |
| Rated Current | 10 amps (RCD is 16 amps, C-13 is 10 amps) |
| Rated Voltage | 250 Volts |
| Frequency | 50 Hz |
| Polarity | 2 Pole 3 Wire |
| Tripping Current | 30 mA |
| Maximum Tripping Time | 30 ms |
| Ambient Temperature Range | -25C to 40C (+5C to 60C for cordage) |
| Reset Type upon Power Loss | Manual (also known as Active or non-Latching) |
| Color | Black |
| Design | Conforms to BS 7071:1992 Protection grade for housing: IP65 Tested according to DIN VDE 0661 and EN61540 |
| Plug | Italian CEI 23-16/VII, Straight, Molded, Black |
| Cordage | 3x1.0 mm ² H05VV-F, Black Jacket |
| Receptacle (Connector) | IEC 60320 C-13, Down Angle, Black |
| Certifications | RoHS and CE |
| Function | Test and Reset Buttons not to be used as ON/OFF switch |

ALL DIMENSIONS ARE IN MILLIMETERS

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

TITLE

RCD CORD SET, IN-LINE STYLE

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS.
NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE
NONE

DATE
12-3-2007

PART NO.
R3B2-M22AD-XXXX

REV
—