



SEV 1011 T23  
SWISS 16 AMP

IEC 60309 6H IP44

|                            |  |
|----------------------------|--|
| Description                | RCD, In-Line Style with Cord   |
| Rated Current              | 16 amps  |
| Rated Voltage              | 250 Volts  |
| Frequency                  | 50 Hz  |
| Polarity                   | 2 Pole 3 Wire  |
| Tripping Current           | 30 mA  |
| Maximum Tripping Time      | 30 ms  |
| Ambient Temperature Range  | -25C to 40C (+5C to 60C for cordage)   |
| Reset Type upon Power Loss | Manual (also known as Active or non-Latching)  |
| Color                      | Black  |
| Design                     | Conforms to BS 7071:1992<br>Protection grade for housing: IP65<br>Tested according to DIN VDE 0661 and EN61540 |
| Plug                       | SEV 1011 T23, Straight, Mounted, Black   |
| Cordage                    | 3x1.5 mm <sup>2</sup> H05VV-F, Black Jacket  |
| Receptacle (Connector)     | IEC 60309 6H IP44  |
| Certifications             | RoHS and CE  |
| Function                   | Test and Reset Buttons not to be used as ON/OFF switch   |

ALL DIMENSIONS ARE IN MILLIMETERS

**WORLD CORD SETS, INC.**

TEL (860)763-2100  
FAX (860)763-1183



www.WorldCordSets.com  
sales@WorldCordSets.com

TITLE

RCD CORD SET, IN-LINE STYLE

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS.  
NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE  
NONE

DATE  
12-3-2007

PART NO.  
R3B2-Q23V-XXXX

REV  
-