



Description	RCD, In-Line Style with Cord
Rated Current	10 amps (RCD is 16 amps, C-15 is 10 amps)
Rated Voltage	250 Volts
Frequency	50 Hz
Polarity	2 Pole 3 Wire
Tripping Current	30 mA
Maximum Tripping Time	30 ms
Ambient Temperature Range	-25C to 40C (-25C to 60C for cordage)
Reset Type upon Power Loss	Manual (also known as Active or non-Latching)
Color	Black
Design	Conforms to BS 7071:1992 Protection grade for housing: IP65 Tested according to DIN VDE 0661 and EN61540
Plug	BS1363A, Angle Type, Molded, Black
Cordage	3x1.0 mm ² H07RN-F, Black Jacket
Receptacle (Connector)	IEC60320 C-15, Straight, Molded or Mounted, Black
Certifications	RoHS and CE
Function	Test and Reset Buttons not to be used as ON/OFF switch

ALL DIMENSIONS ARE IN MILLIMETERS

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

TITLE

RCD CORD SET, IN-LINE STYLE

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS.
NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE
NONE

DATE
12-3-2007

PART NO.
R3B2-R72B-XXXX

REV
-