



IEC 60309 6H IP44

AFSNIT 107-2-D1  
 DANISH 13A  
 CONNECTOR

Description	RCD, In-Line Style with Cord
Rated Current	13 amps (RCD is 16 amps, Connector is 13 amps)
Rated Voltage	250 Volts
Frequency	50 Hz
Polarity	2 Pole 3 Wire
Tripping Current	30 mA
Maximum Tripping Time	30 ms
Ambient Temperature Range	-25C to 40C (-25C to 60C for cordage)
Reset Type upon Power Loss	Manual (also known as Active or non-Latching)
Color	Black
Design	Conforms to BS 7071:1992 Protection grade for housing: IP65 Tested according to DIN VDE 0661 and EN61540
Plug	IEC 60309 6H IP44
Cordage	3x1.5 mm <sup>2</sup> H07RN-F, Black Jacket
Receptacle (Connector)	AFSNIT 107-2-D1, Straight, Mounted, Gray
Certifications	RoHS and CE
Function	Test and Reset Buttons not to be used as ON/OFF switch

ALL DIMENSIONS ARE IN MILLIMETERS

**WORLD CORD SETS, INC.**

TEL (860)763-2100            www.WorldCordSets.com  
 FAX (860)763-1183      sales@WorldCordSets.com

TITLE  
**RCD CORD SET, IN-LINE STYLE**

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS.  
 NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE NONE	DATE 12-3-2007	PART NO. R3B2-V73H-XXXX	REV -
---------------	-------------------	----------------------------	----------