



Description	User Attachable RCD, Plug-Head Style
Plug Configuration	AS / NZS 3112 - 10 Amp
Rated Current	10 amps
Rated Voltage	230-240 Volts
Frequency	50 Hz
Polarity	2 Pole 3 Wire
Tripping Current	30 mA
Maximum Tripping Time	30 ms
Ambient Temperature Range	-
Reset Type upon Power Loss	Manual (also known as Active or non-Latching)
Color	ORANGE
Design	Approval by Dept of Fair Trading Protection grade for housing: IP3X Tested according to AS3190/1997, AS3100/1994
Cordage	Accepts 0.75 to 1.5 mm ² cordage, ordinary duty
Function	Test and Reset Buttons not to be used as ON/OFF switch

ALL DIMENSIONS ARE IN MILLIMETERS

WORLD CORD SETS, INC.	
TEL (860)763-2100	www.WorldCordSets.com
FAX (860)763-1183	sales@WorldCordSets.com
	

TITLE	RCD – USER ATTACHABLE, PLUG–HEAD STYLE
-------	--

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE	DATE	PART NO.	REV
NONE	1-29-2008	RPH-M-AUS10-30R	—