



Description	User Attachable RCD, Plug-Head Style
Plug Configuration	SCHUKO CEE 7/7
Rated Current	16 amps
Rated Voltage	250 Volts
Frequency	50 Hz
Polarity	2 Pole 3 Wire
Tripping Current	10 mA
Maximum Tripping Time	30 ms
Ambient Temperature Range	-25C to 40C
Reset Type upon Power Loss	Manual (also known as Active or non-Latching)
Color	White
Design	Protection grade for housing: IP44 Tested according to DIN VDE 0661 and EN61540
Cordage	Accepts 8 - 10 mm diameter cordage
Grommet	included
RoHS	RoHS compliant
Function	Test and Reset Buttons not to be used as ON/OFF switch

ALL DIMENSIONS ARE IN MILLIMETERS

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

TITLE

RCD – USER ATTACHABLE, PLUG-HEAD STYLE

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS.
NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE
NONE

DATE
12-3-2007

PART NO.
RPH-M-SCHUKO-10W

REV
—